

3

MP40-MP50-P50-P60



mm	Type	DaN	mm	mm	mm x mm	mm x mm	mm	mm	mm	mm	mm	Type	mm	Type	mm
80	R.P. MP40	300	68	47	100x84	80x60	9	4	40	3	8	../2F	113	-	-
100	R.P. MP40	300	78	47	100x84	80x60	9	4	40	3	8	../2F	114	-	-
125	R.P. MP50	300	93	51	100x84	80x60	9	4	50	3	8	../2F	128	-	-
80	R.P. P50	450	85	47	100x84	80x60	9	4	50	3	10	../2F	113	-	-
100	R.P. P50	450	85	47	100x84	80x60	9	4	50	3	10	../2F	114	../2R	99
125	R.P. P50	450	99	51	100x84	80x60	9	4	50	3	10	../2F	128	../2R	100
125	R.P. P60	700	102	61	132x110	105x80	12	5	60	3,5	12	../2F	158	../2R	104
150	R.P. P50	400	113	45	132x110	105x80	11,5	4	50	3	10	../2F	128	../2R	108
150	R.P. P60	700	120	60	132x110	105x80	12	5	60	3,5	12	../2F	157	../2R	107
160	R.P. P60	700	120	60	132x110	105x80	12	5	60	3,5	12	../2F	158	../2R	108
175	R.P. P60	700	143	59	132x110	105x80	12	5	60	4	12	../2F	158	../2R	109
200	R.P. P60	700	143	59	132x110	105x80	12	5	60	4	12	../2F	158	../2R	109

VARIANTI - OPTIONS



/2F

Con freno totale anteriore
Front total stop brake



/2R

Con freno totale posteriore
Rear total stop brake

3

MP40-MP50-MP60-P60

INOX



Con grasso per alta temperatura +230° C.

With grease for high temperature + 230° C.

INOX
STAINLESS STEEL

mm	Type	DaN	mm	mm	mm x mm	mm x mm	mm	mm	mm	Type	mm
80	R.P. MP40	300	68	43	100x84	80x60	9	40	8	.../2F	113
100	R.P. MP40	300	78	42	100x84	80x60	9	40	8	.../2F	114
125	R.P. MP50	300	93	53	100x84	80x60	9	50	8	../2F	128
125	R.P. P60	700	102	61	132x110	105x80	12	60	12	.../2F	158
150	R.P. P60	700	120	62	132x110	105x80	12	60	12	.../2F	157
160	R.P. P60	700	120	62	132x110	105x80	12	60	12	.../2F	158
175	R.P. P60	700	143	61	132x110	105x80	12	60	12	.../2F	158
200	R.P. MP60	500	142	61	132x110	105x80	12	60	12	.../2F	158
200	R.P. P60	700	143	61	132x110	105x80	12	60	12	.../2F	158

VARIANTI - OPTIONS



/2F

Con freno totale anteriore
Front total stop brake